




SPECIAL FURNACE CO INC

20 Kent Road • PO Box 2129 • Aston, PA 19014 • 610.459.9216 • Fax: 610.459.3689 • Web: hotfurnace.com

QDH SERIES



This is actually a photograph of a regular QD furnace. On the QDH the fan and recirculation muffle is on the top.

APPLICATIONS

The QDH Series Dual Chamber Heat Treating furnaces feature a 2350°F (1285°C) high heat chamber for hardening and a 1875°F (1025°C) recirculating chamber for preheating and/or tempering. The over/under configuration saves floor space. The tempering/preheat furnace is mounted on top with the high heat hardening furnace mounted below. Agitated and heated quench tanks are optional. The furnaces achieve high precision by featuring highly accurate controls, mercury contactors for fast cycle times, two zone control (top and bottom) on the hardening furnace, and very even spacing of elements. The preheat/tempering chamber features a powerful fan and recirculation muffle for high uniformity.

**DUAL CHAMBER OVER / UNDER HEAT
TREATING FURNACES 2350°F / 1875°F
(1285°C / 1025°C)**

FEATURES

HIGH TEMPERATURE UNIFORMITY

The hardening furnace is uniform to within +/-20°F (+/-10°C) above 1500°F (815°C). The tempering oven is uniform to within +/-10°F (+/-5°C) above 300°F (148°C).

TWO ZONES AND EVEN ELEMENT PLACEMENT

The elements of both furnaces are divided into top and bottom zones. The control output is routed through two input switches which allow adjustment of the total time on to each zone. There are thermocouples mounted in the top and bottom with a selector switch to read the temperature differential. The elements are evenly spaced on the door, back, sides and bottom for even heating. The elements are supported in proprietary high temperature ceramic element holders. These provide perfect support for the coiled element as well as excellent radiating characteristics. The smooth surface prevents premature failure of the element as it expands and contracts. Elements are iron-aluminum-chrome alloy although nickel-chrome elements are optional.

EFFICIENT MULTILAYERED INSULATION

Both chambers are insulated with 4-1/2" of low K factor refractory firebrick as the primary insulation. This is backed up by 2" of very low K factor mineral wool board on all surfaces except the bottom which has 2" of hard calcium silicate back up for solid hearth support. This yields an excellent combination of strength, insulating quality and fast heat up and cool down time. All refractory is coated with a special facing that prolongs firebrick life and helps prevent spalling and dusting. The refractory sections are available completely shaped for easy replacement without cementing. All sections fit together with engineered heat locks which improve the insulating integrity of the furnace.

HEAVY DUTY INTEGRATED CASE

Both chambers are mounted in one integrated 10 gauge steel case with structural stiffeners and lifting rings. The entire case is primed with 800°F silicone paint and finished in machine enamel.

FAN AND RECIRCULATION MUFFLE

The tempering/preheat furnace features a top mounted four bladed alloy fan. It is belt driven with a 3/4 H.P. motor. A heat dissipator protects the bearings. The removable recirculation muffle is constructed of high temperature 330 alloy steel. This has a reinforced expanded metal bottom for use as the hearth. The muffle protects the work from direct radiation of the elements and creates a recirculation pattern for the air.

DOUBLE PIVOTED PLUG DOORS

Both doors are double pivoted horizontal doors with 1/2" refractory plugs for a superb heat lock around the door seal. The

double pivoting allows the door to be opened so that the hot face stays away from the operator.

DIGITAL PID CONTROL AND HIGH LIMIT SYSTEM

The standard controls are Honeywell UDC 2300 digital PID 3 mode tuning controls. All fuses, transformers, contactors, and controls are housed in a NEMA 1 panel. Quiet, long life mercury power contactors are standard. The thermocouples are Type K Thermocouple break protection is included. Limit switches shut off power when doors are opened or the backs are removed. Control voltage is transformed to 120 volts. A NEMA 13 lighted On/Off switch is included. The control circuit and each power branch circuit are fully fused. A Honeywell UDC 2300 digital high limit back up control with manual reset, back up contactors and separate thermocouple is standard for both chambers. Customer must connect fused power supply to single point on panel.

TESTING AND INSTRUCTIONS

The furnace is power tested to insure proper watt ratings. A complete instruction manual includes easy start up instructions, theory of operation, maintenance instructions, parts list, and a detailed trouble shooting guide. A ladder logic and panel layout diagram are prepared on CAD for easy readability.

WARRANTY

The furnace is warranted for one year except for elements and thermocouples (warranted for 6 months.)

OPTIONS

- **JIC CONTROL OPTION:** Includes a NEMA 12 control cabinet, oil tight switches, panel mounted fused disconnect switch and percentage timers for zones.
- **HIGH K.W.:** Available on hardening furnace.
- **SCR POWER CONTROL:** For greater precision.
- **INERT ATMOSPHERE CONTROL**
- **RAMP/SOAK PROGRAM CONTROLS**
- **TEMPERATURE RECORDERS:** Round and strip
- **VERTICAL DOORS:** Counterbalanced vertical door is available for the tempering/preheat chamber only. Manual hand crank, pneumatic or electric operation.
- **SPECIAL HEARTH:** Silicon Carbide or alloy hearth.
- **AGITATED, HEATED QUENCH TANKS:** These provide superior quenching results. Request QT Bulletin.

SPECIFICATIONS

MODEL NUMBER	HARD CHAMBER ACTUAL DIMEN			HARD CHAMBER UNIFORM INSIDE DIMEN			TEMP CHAMBER INSIDE RECIRC MUFFLE DIMEN			OUTSIDE DIMENSIONS			HARD CHAMB K.W.	TEMP CHAMB K.W.	MAX LOAD LBS	APRX-SHIP WGT
	IW	IH	ID	W	H	D	IW	IH	ID	OW	OH	OD				
QDH 524	16	18	25	12	11	20	11	9	20	54	87	56	13.5	10.0	110	2000
QDH 814	19	15	25	15	9	20	14	6	20	57	84	57	14.0	10.0	125	2300
QDH 824	19	21	25	15	15	20	14	12	20	57	96	57	17.0	12.0	150	2700
QDH 836	19	21	37	15	15	32	14	12	32	57	96	69	22.5	17.5	200	3300
QDH 236	25	21	37	21	15	32	20	12	32	63	96	73	27.0	21.0	300	350

Dimensions are in inches. Weight is in pounds. 240 or 460 volts is normal. 208, 380 and 575 volts are optional. 3 phase is normal although single phase is available. Inside tempering chamber dimensions are also working dimensions for that chamber. Specifications are subject to change without notice.